

SkyEdge® II-C CAPRICORN OUTDOOR

All Weather VSAT Solution

ALL-OUTDOOR VSAT

SkyEdge II-c Capricorn Outdoor is a VSAT satellite communications solution designed for all-weather communications in harsh environments. Its winning combination of an ultra-high-performance VSAT and rugged construction make SkyEdge II-c Capricorn Outdoor the perfect VSAT for the collection and transmission of critical data at remote, unattended outdoor locations. Whether monitoring remote pipeline sections or smart grids, providing video surveillance of facilities, providing backhaul to cellular towers or other uses where information is required for proactive maintenance or security, SkyEdge II-c Capricorn Outdoor is the optimal choice.

WHEN FAILURE IS NOT AN OPTION

Capricorn Outdoor is built to function under the most severe weather conditions. All connectors are hermetically sealed to protect the electronics from water, sand and humidity. By using high-grade industrial components, Capricorn Outdoor provides reliable operation in the most extreme conditions.

ENABLING HIGH-SPEED BROADBAND SERVICES

Capricorn Outdoor is part of SkyEdge II-c Capricorn's family of ultra-high-performance VSATs, designed to deliver high-throughput communications for corporate sites, 2G/3G/LTE cellular towers, POPs and mobility platforms. For 3G and LTE cellular backhauling, Capricorn includes Gilat's patent-pending cellular data acceleration software that enables full LTE speeds on cellular handheld devices. To support these very high return speeds, Capricorn supports both TDMA and SCPC transmission.

Based on SkyEdge II-c Capricorn VSAT technology, Capricorn Outdoor integrates Gilat's considerable product experience with TCP and HTTP acceleration, QoS, high inbound bitrates, improved access schemes and modulations.



Benefits:

- An all-weather satellite modem/router, operational under a wide range of external conditions
- High reliability with industrial-grade components
- Internal thermostatically controlled heater for cold temperatures
- Increased lightning protection
- Weatherproof external connections
- Up to 200Mbps service for 2G/3G/LTE cellular backhauling
- Built-in acceleration for 3G and LTE cellular data services
- On-demand inbound switchover between TDMA and high-speed SCPC carrier

COMPLETE FEATURE SET

Capricorn Outdoor includes a full-featured IP router, advanced application-based QoS, VLANs, and next generation IPv6 networking. To ensure fast Internet and a high-quality user experience, Capricorn Outdoor contains a full set of protocol optimization and application acceleration features, including TCP and HTTP protocol acceleration, compression and embedded web caching technologies. Capricorn Outdoor provides the highest level of transmission security, supporting X.509 terminal authentication and AES-256 bit link layer encryption with dynamic key rotation to protect all user traffic.

ADVANCED VSAT PLATFORM - CORPORATE & ENTERPRISES

Based on the latest generation, multi-core ARM technology, Capricorn Outdoor enables high-speed services up to 200Mbps.

This, combined with the built-in acceleration technologies, is ideal for enterprise applications such as Cellular Backhaul, Mobility services, ISP PoP Locations, Oil & Gas, Video Contribution and Corporate Networking, which demand substantial bandwidth as well as large amounts of packets-per-second.

MAXIMUM SPECTRAL EFFICIENCY

Gilat's innovative transmission technologies deliver exceptional performance and space segment efficiencies. Adaptive transmission in the return direction, enables high on-the-move service availability and maximum bandwidth efficiency at any condition – at beam peak, beam edge, at fade and at different traffic demands. This is achieved by adaptive power control and changes to the carrier symbol rate and ModCod per VSAT on a per time-slot basis.

TECHNICAL SPECIFICATIONS ····

FORWARD CHANNEL

- Standard: DVB-S2 Adaptive Coding and Modulation (ACM)
- Carrier Rate: 1.5Msps-67Msps (235Mbps)
- Modulation: QPSK, 8PSK, 16APSK, 32APSK
- Coding: LDPC, BCH
- **FEC:** 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10

RETURN CHANNEL

- Access Scheme: MF-TDMA, Adaptive Inbound
 Inbound Rates: Symbol rate 128Ksps-6Msps
- Modulation: BPSK, QPSK, 8PSK, 16QAM
- Coding: TPC
- FEC: 1/3, 2/5, 1/2, 2/3, 3/4, 4/5, 6/7

RETURN CHANNEL (SCPC)

- Standard: DVB-S2 Adaptive Coding and Modulation (ACM)
- Carrier Rate: 1.5Msps-40Msps
- Modulation: QPSK, 8PSK, 16APSK
- Coding: LDPC, BCH
- **FEC:** 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10

MODEM INTERFACES

RF Input/Output:

Two female F connectors, 75 Ω RF in frequency - 950-2300MHz RF out frequency - 950-2300MHz DISEqC

Data Interfaces:

4 x Ethernet 10/100/1000BaseT RJ-45, 802.1g VLAN

Management Interface:

Web-based local management Full FCAPS management Remote software upgrades over the air SNMP

ENHANCED FEATURES

IP Features:

IPv4/IPv6, TCP, UDP, ICMP, DHCP, NAT/PAT, DNS Caching, cRTP, IGMPv2, SIP, DiffServ, VLANs, RIPv2, Static Routes

QoS:

Per VSAT and per Managed Group, CIR, MIR, CBR, DiffServ and priority-based queuing, application-based priority

Security:

AES-256 bit encryption IPSEC Client ACL Firewall X.509 Terminal Authentication

Application Acceleration and Protocol Optimization:

TCP acceleration

HTTP web pre-fetch acceleration and compression GTP cellular data acceleration

ENVIRONMENTAL AND MECHANICAL

- Operation Input Voltage: DC: 48V, DC: 24V, and AC
- Operating Temperature: -40°C to +60°C
- Humidity: Up to 100%
- **Dimensions:** 200 x 122 x 400mm (WxDxH)
- Weight: 6.3 Kg
- Certifications: CE, FCC, EMC

TX/RX (ODU)

- Frequency Bands: C, Ku, Ka
- Transmitter Power: Via IDU 24V or 48V DC Insertion^
- Antenna Size: 0.76m and higher



To learn more about SageNet the SkyEdge II-c Capricorn Outdoor, visit our website, www.sagenet.com, or call 1-866-480-2263.

SkyEdgeII-cCapricornOutdoorDS010819

[^] Requires selection of appropriate IDU part number